

The version attribute enables the parser/interpreter of an SDA deployment descriptor to distinguish between different versions of this DTD.

-->

```
<!ATTLIST j2ee-deployment-descriptor
  version CDATA #FIXED "1.0"
>
```

<!--

The display-name element contains a short name for the parent element that is intended to be displayed by SDM.

Each occurrence of this element within the J2EE specific part of this DTD is accompanied by an occurrence of a corresponding display-name element in the DTD of the standard J2EE deployment descriptors.

Therefore, within the J2EE specific part of a concrete SDA deployment descriptor, the contents of the display-name elements have to coincide with the contents of their corresponding elements in the standard J2EE deployment descriptors.

-->

```
<!ELEMENT display-name (#PCDATA)>
```

<!--

The description element is used to provide text describing the parent element. This text should include any information that will be useful for the deployer. It is intended to be displayed by SDM.

Each occurrence of this element within the J2EE specific part of this DTD is accompanied by an occurrence of a corresponding description element in the DTD of the standard J2EE deployment descriptors.

Therefore, within the J2EE specific part of a concrete SDA deployment descriptor, the contents of the description elements have to coincide with the contents of their corresponding elements in the standard J2EE deployment descriptors.

-->

```
<!ELEMENT description (#PCDATA)>
```